



[7] ADDED AS SECONDARY PROCEDURE.

- U6 IS 4066 TYPE.
 - U4, U5 ARE 4082 TYPE 4-INPUT AND GATES.
 - U1-U6, PIN 7 IS V-, PIN 14 IS GROUND.
 - U1-U3 ARE 4584 TYPE SCHMITT TRIGGERS.
 - U1-U3 ARE 1N4003 (EXCEPT AS NOTED).
 - ALL DIODES ARE 1N4003 (EXCEPT AS NOTED).
 1. ALL CAPACITORS IN MICROFARADS (EXCEPT AS NOTED).
- NOTES: UNLESS OTHERWISE SPECIFIED**

LAST USED LIST

SYM	00177
C	1-4
D	1-27
R	1-23
S	1-7
U	1-6

CARVIN
1155 INDUSTRIAL AVE.
ESCONDIDO, CA 92029
(619) 747-1710
FAX 747-9065

Quad X-Amp

Schematic 84-00177	FS-77 Footswitch
DRAWN BY: John L. Murphy	DATE: 13JUN91
APPROVED:	DATE:
PCB NO: 30-00177	REV: A
ASSY. NO: 80-00177	REV: A
REVISED BY: C. McEUIEN	DATE: 25FEB92