## Fender

FRS. BO F

## FENDER "PRO-REVERB-AMP AA 165" LAYOUT VOLTAGES READ TO GROUND WITH ELECTRONIC VOLTMETER VALUES SHOWN + OR - 20% INTENSITY SPEED REVERB BASS TREBLE VOLUME VIBRATO BASS TREBLE VOLUME NORMAL TO ALL 6 3 VOLT HEATERS 250K-A2-35 50K-RA2-35 3.0M RA 100 K-L 250K-A 250KA2-35 0015 10012 SREEN 25 50 YELLO RED-YELLOW GREEN-YELLOW 6L6GC 6L6GC 12AT7 12AX7 7025 **GZ34** 7025 7025

NOTE: ALL RESISTORS 1/2 WATT 10% TOLERANCE, IF NOT SPECIFIED.

.047 - 600

GROUND SWITCH

NOTE: ALL CAPACITORS AT LEAST 400 VOLT RATING IF NOT SPECIFIED.

VIBRATO REVERB REVERB PEDAL PEDAL OUTPUT INPUT

FENDER MUSICAL INSTRUMENTS
A DIVISION OF COLUMBIA RECORDS DISTRIBUTION CORP.
FULLERTON, CALIFORNIA
U.S.A.

## Fender

