



- NOTES
1. ALL RES. 1/2 W UNLESS NOTED.
 2. ALL CAP. IN MFD. UNLESS NOTED.
 3. VOLTAGES ± 10% MEASURED WITH VTVM.
- △ ADJ FOR 25MA COLLECTOR CURRENT
 ▽ ADJ FOR 1DB DROP AT 20W

ITEM	PART NO	DESCRIPTION	ORIG DWG
R1	10K	RESISTOR	8-12-66
R2	SELECTED		
R3	10K		
R4	4.7Ω		
R5	350Ω 1W		
R6	470Ω 2W		
R7	2.7		
R8	470Ω 2W		
R9	2.7		
R10	47Ω		
R11	47Ω		
R12	100K		
R13	100		
R14	4.7K		
R15	SELECTED		
C1		CAPACITOR	
C2	.05 600V		
C3	35V 4000 MFD		
C4	35V 4000 MFD		
C5	250/25V		
C6	250/25V		
C7	15V 1MFD		
Q1	7-4	TRANSISTOR	
Q2	7-1		
Q3	7-1		
SR1	7-8	SIL RECT	
J1	15-2	OPEN CKT JACK	
F1	3AG 1.5A	FUSE	
F2	3AG 3A		
F3	3AG 3A		
L1	13-2	PILOT LAMP	
SO-1	9-2	POWER INPUT	
SO-2	9-1	POWER OUTPUT	
T-1	PT79B	POWER TRANS.	
T-2	OT433	DRIVER TRANS.	
THE STANDEL CO.			
SCHEMATIC DIAGRAM MODEL PB25			
DRAFTSMAN L.D.S.	CHECKED	APPROVED	DATE